

ATTACHMENT 2-G

MRF PRODUCT QUALITY STANDARDS

The following Product Quality Standards are for to be followed by the Contractor to ensure that there is effective recovery of materials and that quality Products are produced by the single-stream processing system and marketed by the Contractor. All measurements of percentage in the Product Quality Standards are by weight.

Fiber

1. At a minimum, 75% of the newspaper feed into the processing system will be captured and baled separately from mixed paper.
2. Product sold by the Contractor will meet the ISRI specifications for #8 newspaper, #2 mixed paper and OCC or the Contractor will manufacture a commodity of sufficient quality that sales revenue per ton are equal to or greater than the average market price paid to other processors in the Bay Area selling the same commodity grade as determined by a local market survey of other processors conducted by the SBWMA at the SBWMA's discretion.
3. Should prices fall below the average commodity price or the Contractor's loads are rejected or down graded by buyers, the Contractor will be required to meet the ISRI product quality specifications.
4. Not more than 1% of fiber materials (defined as whole or intact sheets of fiber and does not include shredded paper) fed into the Processing System shall be disposed as residue or trash.
5. At a minimum, 90% of the paper (excluding shredded and paper recovered as newspaper or corrugated cardboard) arriving at the facility will be captured and baled as mixed paper.
6. At a minimum, 95% of the corrugated cardboard arriving at the facility will be captured and baled as OCC.

Container Glass. Glass product sold by the Contractor will have less than 10% non-glass contamination and meet the minimum standards for the State California Redemption Value (CRV).

Aluminum. At a minimum, 99.5% of the aluminum cans fed into the processing system shall be recovered and processed and be free of contaminants.

PET. At a minimum, 98% of the PET bottles collected shall be recovered as PET Product. PET product shall contain less than 2% contaminants. Not more than 1% by weight of all collected PET shall be disposed as residue.

HDPE. At a minimum, 98% of the HDPE containers collected shall be recovered as HDPE Product. HDPE product shall be sorted into natural and colored and each Product shall contain less than 2% contaminants. Not more than 1% by weight of all collected HDPE shall be disposed as residue.